

Appl. No. 10/090,576
Amdt. Dated Jan. 31, 2005
Reply to Final Office Action of December. 02, 2004

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An in situ tumor temperature profile measuring probe, comprising:

an elongated rod including a pair of opposite end portions, an outer insulating layer having a plurality of spaced apart holes defined therein at one of said opposite end portions of said rod, and a common electrical input lead extending between said opposite end portions of said rod and disposed below said holes and having portions exposed at said holes, said common electrical input lead being adapted to provide an electrical input signal;

a plurality of spaced apart microscopic thermal sensors each formed within one of said holes of said outer insulating layer of said rod in electrical contact with said common electrical input lead of said rod, each of said thermal sensors being adapted to receive the electrical input signal from said common electrical input lead, to sense in situ the temperature of biological matter adjacent to where said thermal sensor is placed and to produce an electrical output signal correlated to the temperature sensed; and

a plurality of microscopic electrical output leads each mounted to said outer insulating layer of said rod in electrical contact with a different one of said thermal sensors and extending to the other of said opposite end portions of said rod, each of said electrical output leads being adapted to receive the electrical output signal from said one of said thermal sensors and output the electrical output signal to means for collecting the output signals and forming a temperature profile of the biological matter.

2. (Original) The probe of claim 1 in which said common electrical input lead of said rod is a hollow tube made of an electrically conductive material.

3. (Original) The probe of claim 1 in which said common electrical input lead of said rod is an elongated strip made of an electrically conductive material.

4. (Original) The probe of claim 1 in which said holes and said thermal sensors therein are arranged in a linear array in which said thermal sensors are aligned axially with respect to one another along said rod.

5. (Cancelled)

Appl. No. 10/090,576

Amdt. Dated Jan. 31, 2005

Reply to Final Office Action of December. 02, 2004

6. (Original) The probe of claim 1 in which each of said thermal sensors and said electrical output leads is micron-scale in size.

7. (Original) The probe of claim 1 further comprising an exterior insulating layer covering at least said electrical output leads.

8. (Currently Amended) An in situ breast temperature profile measuring probe assembly, comprising:

a an in situ measuring probe including

a pair of opposite end portions, an outer insulating layer having a plurality of spaced apart holes defined therein at one of said opposite end portions of said rod, and a common electrical input lead extending between said opposite end portions of said rod and disposed below said holes and having portions exposed at said holes, said common electrical input lead being adapted to provide an electrical input signal,

a plurality of spaced apart microscopic thermal sensors each formed within one of said holes of and on said outer insulating layer of said rod in electrical contact with said common electrical input lead of said rod, each of said thermal sensor being adapted to receive the electrical input signal from said common electrical input lead, to sense in situ the temperature of biological matter adjacent to where said thermal sensor is placed and to produce an electrical output signal correlated to the temperature sensed, and

a plurality of microscopic electrical output leads each mounted to said outer insulating layer of said rod in electrical contact with a different one of said thermal sensors and extending to the other of said opposite end portions of said rod, each of said electrical output leads being adapted to receive the electrical output signal from said one of said thermal sensors and output the electrical output signal to means for collecting the output signals and forming a temperature profile of the biological matter;

a hollow needle insertable into biological matter and having opposite ends and an interior passageway defined through said hollow needle which is open at each of said opposite ends thereof so as to adapt said hollow needle to receive said measuring probe through said interior passageway and guide said one end portion of said rod of said measuring probe into the biological matter; and

an electrical connector for providing an interface between said electrical output leads of said measuring probe and a computer, said electrical connector being adapted to receive said electrical output signals from said electrical output leads of said measuring probe and transmit the temperatures sensed by said thermal sensors of said measuring probe to the computer for collecting said output signals and forming a temperature profile of the biological matter.

Appl. No. 10/090,576

Amdt. Dated Jan. 31, 2005

Reply to Final Office Action of December. 02, 2004

9. (Original) The assembly of claim 8 in which said common electrical input lead of said rod of said measuring probe is a hollow tube made of a first electrically conductive material.

10. (Original) The assembly of claim 8 in which said common electrical input lead of said rod of said measuring probe is an elongated strip made of a first electrically conductive material.

11. (Original) The assembly of claim 8 in which said holes and said thermal sensors of said measuring probe are arranged in a linear array in which said thermal sensors are aligned axially with respect to one another along said rod.

12. (Cancelled)

13. (Original) The assembly of claim 8 in which each of said thermal sensors and said electrical output leads of said measuring probe is micron-scale in size.

14. (Original) The assembly of claim 8 in which said measuring probe also includes an exterior insulating layer covering at least said electrical output leads.

15. (Original) The assembly of claim 8 in which said hollow needle is removable from said measuring probe upon insertion of said measuring probe into the biological matter.

16. (Currently Amended) A method of measuring an in situ tumor temperature profile, said method comprising the steps of:

providing a common electrical input signal;

receiving the common electrical input signal at spaced apart locations within biological matter;

sensing in situ temperatures of the biological matter at the spaced apart locations within the biological matter;

producing a plurality of electrical output signals corresponding to the respective temperatures sensed; and

transmitting the electrical output signals produced to a computer for collecting data.

17. (Original) The method of claim 16 further comprising the step of:

forming a temperature profile of the biological matter.

18. (Original) The method of claim 17 further comprising the step of:

Appl. No. 10/090,576

Amdt. Dated Jan. 31, 2005

Reply to Final Office Action of December. 02, 2004

using the temperature profile of the biological matter to determine whether a tumor is present and what type of a tumor may exist in the biological matter.

Claims 19-22(canceled)